

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
5 February 2004 (05.02.2004)


PCT

(10) International Publication Number
WO 2004/011145 A1

- (51) International Patent Classification⁷: **B01L 3/00**
- (21) International Application Number:
PCT/US2003/023426
- (22) International Filing Date: 25 July 2003 (25.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/398,689 26 July 2002 (26.07.2002) US
- (71) Applicant (for all designated States except US): ARIZONA BOARD REGENTS, a body corporate of the State of Arizona, acting for and on behalf of ARIZONA STATE UNIVERSITY [US/US]; Box 873511, Tempe, AZ 85287 (US).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): McKELVY, Michael, J. [US/US]; 431 N. Diane Court, Chandler, AZ 85226 (US); DIEFFENBACHER, Jason [US/US]; 1114 E. Gwen Street, Phoenix, AZ 85042 (US); WOLF, George, H. [US/US]; 616 S. Esquire Way, Mesa, AZ 85205 (US); CHIZMESHYA, Andrew, V. [CA/US]; 702 W. Curry Street, Chandler, AZ 85225 (US).
- (74) Agent: ONEY, Richard, E.; Fennemore Craig, 3003 North Central Avenue, Suite 2600, Phoenix, AZ 85012-2913 (US).
- (81) Designated States (national): CA, JP, US.
- (84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

[Continued on next page]

(54) Title: MICROREACTOR WITH CONTROLLABLE PRESSURE AND TEMPERATURE FOR *IN SITU* MATERIAL INVESTIGATIONS



(57) Abstract: A microreactor (10) for investigation of material reactions and properties includes a core body (12) defining a chamber (22) adapted to contain one or more sample materials and having a fluid passageway (52) from the chamber to the exterior of the core body. The chamber is in fluid communication with an external manifold (50) whereby gases, liquids or fluids can be injected and their activities can be controlled externally from ambient conditions to 400 degrees Celsius and 4,500 psi. Transparent windows (30a, 30b) in the core body permit continuous visual access to the chamber, allow direct probe beam interaction with sample during a reaction or observation, and external detection of the probe beam to investigate *in situ* reaction processes.

10/523 233

WO 2004/011145 A1



Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations CA, JP, European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR)*
- *of inventorship (Rule 4.17(iv)) for US only*

Published:

- *with international search report*

(48) Date of publication of this corrected version:

6 May 2004

(15) Information about Correction:

see PCT Gazette No. 19/2004 of 6 May 2004, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.